



NTD750-2

The whole design concept, construction and performance of the NTD-750 is dedicated to producing a standard industrial vacuum cleaner that will provide totally reliable performance in all standard industrial applications. Be it boiler cleaning, floor cleaning, machine maintenance, high level cleaning, metalworking, dirt, dust or debris, it will take it all in its stride as standard.

The exclusive Structofoam power head incorporating two Twinflo' bypass motors provides exceptional performance and the Nucable replaceable cable system is standard, allowing quick cable replacement in the event of accidental damage.

Two large, standard filters ensure that what goes in stays in and, in addition, giant additional Microflo' dust bags are available.

The standard container is all-steel, finished in Nutex, a specially formulated epoxy resin coating providing extreme durability and long service life. The container is mounted on, but easily removed from, our all-steel heavy-duty chassis equipped with large transit wheels.

The standard accessory kit is to a full 38mm (1 1/2") specification.

Motor	Power	Airflow	Suction	Capacity	Range	Weight	Dimensions
2400W	230V AC 50/60Hz	80 L/sec	2500mm	35L	26.8m	22.8Kgs	510 x 510 x 960mm

Also available 115V/120V specification.

NTD750C-2

Many of the NTD applications involve the collection of substantial volumes of various materials with a high content of low or sub micron particulate.

To upgrade operational performance in fine dust environments, an additional Cyconic Separation Kit can be supplied or retro-fitted to improve the function of the machine in these specialised circumstances.



Motor	Power	Airflow	Suction	Capacity	Range	Weight	Dimensions
2400W	230V AC 50/60Hz	80 L/sec	2500mm	35L	26.8m	25.2Kgs	510 x 510 x 1045mm

NTD750M-2

Although the performance standard of the NTD-750 is exceptionally high, there are applications such as the pharmaceutical industry where the dust being collected could constitute a health hazard.

To allow for these applications we have, by the simple addition of our HEPA filtration module, provided up to 99.997% filter efficiently but without detracting from the convenience and ease of use of this machine size.

The Structofoam, Twinflo' two-motored power head, the container and chassis all meet the full 750 specification in every detail and the accessory kit is to our full 38mm (1 1/2") commercial standard.

The golden rule in the case of dusts that could be injurious to health is to be safe and select the NTD-750M series or, in the case of smaller machines, select the MFQ-370 which is to the same high filtration standard.



Motor	Power	Airflow	Suction	Capacity	Range	Weight	Dimensions
2400W	230V AC 50/60Hz	80 L/sec	2500mm	35L	26.8m	24.2Kgs	510 x 510 x 960mm

Also available 115V/120V specification.